

Tulikivi Soapstone Heaters - American Line - Prices and Technical Specifications



	Suggested Retail Price	Weight	Height	Footprint		Bakeoven		Firebox		Firewood Length	Load per Firing	Heat Release Duration			Ordering Information
				Width	Depth	W	D	W	D			@ 100%	@ 50%	@ 25%	
	USD	lb	in.	in.	in.	in.	in.	in.	in.	in.	lb				code
Small Models															
TU1000 4 feet in height, base vent	\$4,990	2,085	48.4	33.1	18.9			12.2	9.6	10	17	2 hrs	10.5 hrs	18 hrs	TU1000
TU1000 5 feet in height, top vent	\$6,290	2,675	60.2	33.1	18.9			12.2	9.6	10	21	2 hrs	13 hrs	23 hrs	TU1000T
TU1450 5 feet 3 inches in height, base vent	\$7,190	2,950	62.6	35.4	18.9			12.2	9.6	10	24	3.5 hrs	12.5 hrs	22 hrs	TU1450
TU1450 5 feet 3 inches in height, top vent	\$7,190	3,050	62.6	35.4	18.9			12.2	9.6	10	24	2 hrs	13 hrs	23 hrs	TU1450T
Mid-sized Models															
TU2200 5 feet in height, base vent	\$7,990	4,050	60.2	40.2	23.6			15.7	14.4	14	32	4.5 hrs	17.5 hrs	26 hrs	TU2200
TU2200 5 feet in height, top vent	\$7,990	3,950	60.2	40.2	23.6			15.7	14.4	14	32	4.5 hrs	14.5 hrs	25 hrs	TU2200T
TU2200 6 feet in height, top vent	\$8,990	4,600	72.0	40.2	23.6			15.7	14.4	14	37	n/a	n/a	n/a	TU2200T/51
TLU2000 5 feet 5 inches in height, with bakeoven, base vent	\$11,990	4,630	65.0	36.6	29.5	15.4	18.3	14.4	12.0	12	37	5.5 hrs	20.5 hrs	31.5 hrs	TLU2000/91
Large Models															
TTU2700 6 feet in height, top vent	\$10,990	5,685	72.0	40.2	29.5			15.7	14.4	14	45	5 hrs	21.5 hrs	32.5 hrs	TTU2700/4
TTU2700 7 feet in height, with double door firebox, top vent	\$12,990	6,550	83.9	40.2	29.5			15.7	24.8	20	52	5 hrs	18.5 hrs	30 hrs	TTU2700
TTU2700 7 feet in height, with bakeoven, top vent	\$13,490	6,350	83.9	40.2	29.5	16.5	17.1	15.7	14.4	14	51	5 hrs	18.5 hrs	30 hrs	TTU2700/75
TTU2700 7 feet in height, with double door firebox and bakeoven, top vent	\$14,990	6,700	83.9	40.2	29.5	16.5	17.1	15.7	24.8	20	54	5 hrs	18.5 hrs	30 hrs	TTU2700/5
TLU2450 5 feet 6 inches in height, with bakeoven, base vent	\$14,990	6,260	66.1	42.5	35.4	17.7	21.9	15.7	14.4	14	50	6 hrs	23.5 hrs	36 hrs	TLU2450/1
Accessories															
Soapstone four-sided bench for TTU2700	\$3,690	1,780	16.5	63.8	53.1										2700/6
Soapstone two-sided bench for TU2200 (adds 2 3/8 inches to heater height)	\$1,265	550	14.2	68.5	27.8										see dealer
Soapstone chimney element, square	\$290	150	11.8	15.4	15.4										JO70US
Soapstone tiles, per box of 9 tiles	\$199	55	0.4	11.8	11.8										ML10L
Stainless steel chimney damper 6" dia.	\$335	7													1270
Stainless steel chimney damper 7" dia.	\$350	7													1272
Stainless steel chimney damper 8" dia.	\$360	8													1275
Ash door conversion kit for outside air	\$88	3													K14
Electric elements 2kW	\$1,090	6													5123
Electric elements 3kW	\$1,290	12													5150

Additional Information

Tulikivi Soapstone Heaters get assembled on site by a Tulikivi installer. Suggested Retail Prices do not include delivery, on-site assembling, structural support, chimney and optional components such as heat shields, hearth tiles, benches and other accessories. All measurements converted from millimeters. Numbers for Weight and Heat release duration are rounded.

Performance data according to "EN – Declaration of Performance". All models tested to European Standard EN15250:2007. TU1000T and TU1450T tested together. TTU2700, TTU2700/5 and TTU2700/75 tested together.

"Max load per firing" is based on 8 pounds of firewood per 1000 pounds of heater weight. Firings must be at least 10 hours apart.

"X hrs @ 100%" means maximum heat output will be delivered for X hours (after it is reached).

"X hrs @ 50%" means at least 50% of maximum heat output will be delivered for X hours (after maximum heat output is reached).

"X hrs @ 25%" means at least 25% of maximum heat output will be delivered for X hours (after maximum heat output is reached).

Recommended flue diameters : 6" or 7" for small models, 7" or 8" for medium sized and large models. Minimum chimney height (measured from the floor) : 20 feet for models with bakeovens, 15 feet otherwise.

Clearances to combustibles : 20" to the back, 14" to the sides, 10" to the top and 48" to the front. Clearances can be reduced to 3" with a Tulikivi specified heat shield. Clearance for soapstone chimney elements is 1".

Floor protection : 3/8 minimum thickness of non-combustible material, extending 8" from the sides, 8" from the back (unless there is a heat shield) and by 16" from the front of the heater.

Tulikivi Soapstone Heaters carry a 5-year manufacturer's warranty and are UL/ULC safety tested and listed. Like all Masonry Heaters, Tulikivi Soapstone Heaters are exempt from compliance to EPA NSPS 2015.

